

DATA SHEET

Baratta BMT-450 Electric 450 litre Bratt Pan with Auto Mixing | Auto Tank Tilt and Lid Lift

454101214

baratta



Build

- Heavy-duty robust construction built entirely from heavy gauge AISI 304 / 316 stainless steel and designed for intensive industrial use.
- Constructed with the highest quality materials and components, ensuring longevity, ease of maintenance, and adherence to the highest hygiene standards for cleaning and sanitization
- Designed and constructed with best-in-class insulation layers that minimize heat loss, optimize energy efficiency, and enhance cooking yield
- Heavy duty 450 litre corrosion resistant tank constructed entirely from heavy-gauge AISI 316 stainless steel and ideal for cooking acidic ingredients and with superior thermal efficiency.
- Thick-Rayed AISI 316 stainless steel bottom base enhances thermal efficiency and stability, ensuring optimal heat distribution and durability during intensive use.
- AISI 304 heavy-gauge stainless steel lid is completely motorised lid and includes two-hand safety controls
- Electric tank tilting mechanism powered by a robust gear motor, enabling effortless emptying of the tank.
- Heavy-duty AISI 316 stainless steel mixing arms with food-grade Teflon scrapers on the bottom and optional scrapers on the walls of the tank. These mixing arms ensure seamless mixing, prevent food adhesion, and operate autonomously without user intervention.
- The mixing arms are controlled by a speed regulation knob, offering full variable speed capabilities. Powered by a durable variable-speed direct drive motor with an inverter, it supports a wide range of cooking applications and includes a reverse function for added versatility.
- Direct electric armoured heating elements, positioned directly beneath the cooking base, are -powered by a 43 kW system, delivering optimal cooking power and precise temperature control.
- Product temperature probe controls the cooking temperatures from 50°C to 220°C using a side-mounted probe, ensuring consistent internal cooking temperatures.
- The cooking surface temperature probe measures and controls temperatures from 50°C to 300°C, ensuring perfect braising results.
- The dual temperature management system integrates both temperature controls to guarantee perfect cooking results. The product temperature probe regulates food temperatures, while the surface temperature probe measures and controls the cooking plate temperature, ensuring perfect synergy for braising, grilling, and consistently cooked food every time
- Safety thermostat prevents overheating by automatically shutting off the heating elements if temperatures exceed safe levels, ensuring reliable and secure operation.
- IP54 water protection rating safeguards the Bratt pan against dust and water splashes, making it suitable for various kitchen environments.
- Safety lamp alerts operators if any electrical phase issues occur ensuring enhanced safety.
- Durable electromechanical control panel enables precise programming of cooking functions, including thermostat adjustments on both the core product temperature and surface temperature, cooking time adjustments, tank tilting, and mixer arm rotation speeds. Simple and intuitive, controls are positioned above the unit for easy cleaning, reliability, and user-friendly operation.
- Acoustic alert signals the completion of a programmed cooking cycle
- Extensive range of options and accessories to meet the every possible application.
- Backed by over 50 years of industry experience, Baratta continually innovates to exceed standards for strength, functionality, and maintenance, affirming its leadership in high-quality kitchen solutions.

Technical specifications

External Size	
External Width	2010mm
External Depth	1586mm
External Height	1150mm
Weight	
Net weight	
package weight	
Technical Features	
Tank Capacity	450 Lt
Tank Tilt Type	Automatic
Lid Lift Type	Automatic
Control Type	Electromechanical
Product Temperature Probe	50°C to 220°C
Surface Temperature Thermostat	50°C to 300°C
Connection requirements electric	
Electrical connected loads	43 kW
Voltage	400/3+N/50
Plug Supplied	No
Connection requirements Water	
Cold Water Connection	1/2" M
Hot Water Connection	1/2" M
Build Inclusions	
Core Tank Probe	✓
Core Temperature Probe	✓
Warranty	
2 Year Warranty	2 years parts and labour

**Subject to a preventitive maintenance plan*

DATA SHEET

Baratta BMT-450 Electric 450 litre Bratt Pan with Auto Mixing | Auto Tank Tilt and Lid Lift

454101214

baratta

Options

Leg Options

☐	Lockable Wheel Set	
	Model: KR-4	SKU: 456131030
☐	Adjustable Flanged Feet	
	Model: PFT-1	SKU: 456131015



Hand Shower

☐	Hand Shower External	
	Model: DES	SKU: 456131228
☐	Hand Shower Retractable	
	Model: DFS	SKU: 456131230




Drain Filter

☐	Drain Filter for tank ø 930 mm	
	Model: FS-930	SKU: 456131209




Drain Tap

☐	2" Drain Tap	
	Model: MDS-1	SKU: 456131245
☐	Washout Valve 2" DIN50 Connection	
	Model: DS2-50	SKU: 456131251




Lid Options

☐	Lid Hole with Grid	
	Model: CCI	SKU: 456130850
☐	Insulated Cover ø 900 mm	
	Model: CCI-90	SKU: 456130825



Mixing Options

☐	Additional Lateral Tank Wall Scraper	
	Model: MBL-450R	SKU: TBA
☐	Complete Mixing Set including Lateral scrapers	
	Model: MBLL-450R	SKU: TBA
☐	Additional Lateral Wing Mixer	
	Model: MAO-450R	SKU: 457010172
☐	Additional Mixer for solid parts	
	Model: MPS-450R	SKU: 457010258



Control Panel Cover


☐	Control Panel Cover	
	Model: CPC	SKU: 456131135

DATA SHEET

Baratta BMT-450 Electric 450 litre Bratt Pan
with Auto Mixing | Auto Tank Tilt and Lid Lift

454101214

baratta



1	Lid
2	Water mix tap
3	Heart probe
4	Hot water connection 1/2" M
5	Cold water connection 1/2" M
6	Cord connector
7	Emergency stop
8	Main switch
9	Power on pilot lamp
10	Push button start
11	Stop pilot lamp

12	Heart probe thermostat
12a	Tank thermostat
13	Timer
14	Speed mixing regulator
15	Tilting selector
16	Mixing selector
17	Opening lid system
18	Opening lid selector
18a	Button for lid opening
19	Phase control lamp