

DATA SHEET

Lotus FTL-916GS Gas Superchrome 1600mm Hotplate on base

09231654

90-SERIES

☐ LPG

☐ NAT


Build

- Heavy-duty construction made from premium CrNi 18/10 AISI 304 stainless steel with Scotch-Brite satin finish. It features a 2mm thick worktop, rounded edges, chrome details, and a rear splashback.
- Waterproof chromed knobs with an IPX5 waterproof rating
- Superchromed Hotplate (MOCA Approved), combining FE430B Steel and FE510C Chrome Steel, delivers best-in-class heat-up performance, along with superior durability and strength
- Burners with Piezoelectric ignition and Pilot light offering thermostatic temperature control between 50°C and 300°C, and equipped with thermostatic and thermocouple safety
- Designed for easy maintenance and serviceability, with all parts accessible by simply removing the front control panel.
- Fittings - Appliance is supplied with both LPG and Natural Gas conversion jets and adjustable feet.
- High efficiency 128 Mj/hr thermostatically controlled burners
- Removable Large capacity liquid grease collectors

Options

Door Options

☐	Right door 400mm
	Model: P-74/94-DX SKU: 08430400
	Right door 400mm
	Model: P-74/94-DX SKU: 08430400
	Left door 400mm
	Model: P-74/94-SX SKU: 08430401
	Left door 400mm
	Model: P-74/94-SX SKU: 08430401



Technical specifications

External Size

External Width	1600mm
External Depth	900mm
External Height	900mm

Weight

Net weight	
Package weight	266kg

Technical Features

Burner[s] Power	128 Mj/hr
Temperature	50°C - 300°C
Plate Size	150.5m x 65cm

Connection requirements Gas

Gas Consumption	128 Mj/Hr
Gas Connection	1/2" M GAS

Warranty

2 Year Warranty	2 years parts and labour
-----------------	--------------------------

**Subject to a preventative maintenance plan*

90-SERIES

A	Data plate
C	Gas connection ISO 7-1 1/2" M