

## Two Solid Swing Door CounterLine

**Range:** BackBar

**SKOPE ID:** CL002S

**Dimensions:** 1585 mm (W) × 680 mm (D) × 830 mm (H)\*

**Capacity:** 345 L

\* Height with castors is adjustable from 820 to 840.

**Project:** \_\_\_\_\_

**Item #:** \_\_\_\_\_



A solid door under-counter bar fridge designed to merchandise ready-to-serve cold beverages and food in bars, restaurants, clubs, pubs, and cafés. With M1 compliance it is engineered to serve cold food and drinks at 1°C to 4°C (or adjustable up to 15°C) in ambient environments of up to 40°C. Made from powder-coated, galvanised steel with colour options, it can also be upgraded to full stainless-steel construction. The doors and cabinet are fitted with built-in retractable tabs to enable locking via padlock. The fridge uses R290 natural refrigerant for ultra-low energy consumption, low heat discharge and low noise output and can be provided in remote versions. The side-mounted fully removable refrigeration cartridge (with left and right options) is front-breathing and can be removed in line with best practice for safe servicing of flammable refrigerants. The fridge includes a controller that connects to a free app to enable the user to set temperatures and alerts, monitor temperatures and energy, and more. The fridge is certified to all Australian and New Zealand refrigeration and electrical safety standards.



Warranty




Natural Refrigerant



GEMS



SKOPE-connect



### Cabinet

|            |                                                                                    |                                 |
|------------|------------------------------------------------------------------------------------|---------------------------------|
| Type       | CounterLine                                                                        |                                 |
| Finish     | Powder-coated galvanised steel or stainless steel                                  |                                 |
| Insulation | Type                                                                               | PU foam                         |
|            | Thickness (mm)                                                                     | 50                              |
|            | Blowing Agent                                                                      | Cyclo-iso pentane (C5H10/C5H12) |
| Doors      | Type                                                                               | Solid swing door                |
|            | Opening Size                                                                       | Height (mm) 538                 |
|            |                                                                                    | Width (mm) 511                  |
| Shelving   | Four adjustable height powder-coated wire shelves<br>4 x outer shelf (547W x 530D) |                                 |
| Lighting*  | 1 x 16 W dimmable, cool white (5500-6500K) LED strip on cabinet ceiling            |                                 |

### Dimensions†

|                | External                      | Internal | Packed |
|----------------|-------------------------------|----------|--------|
| Width (mm)     | 1585                          | 1120     | 1630   |
| Depth (mm)     | 680                           | 565      | 730    |
| Height (mm)    | 820 to 840 (standard castors) | 545      | 900    |
|                | 725 (plinth mount)            |          |        |
| Weight (kg)    | 135                           |          | 150    |
| Capacity (L)   | 345                           |          |        |
| Footprint (m²) | 1.08                          |          |        |

### Ventilation (mm)

| Top | Not required | Sides | Not required | Rear | Not required |
|-----|--------------|-------|--------------|------|--------------|
|-----|--------------|-------|--------------|------|--------------|

### Product Loading

|         |            |     |               |     |
|---------|------------|-----|---------------|-----|
| Facing  | 330 ml can | 32  | 600 ml bottle | 28  |
| Loading | 330 ml can | 256 | 600 ml bottle | 196 |

\* Accessible via the free SKOPE-connect™ app.

† Allow for dimensional tolerances when installing the cabinet(s).

### Performance

|                                  |                                   |      |
|----------------------------------|-----------------------------------|------|
| Product Temperature Range (°C)   | 1 to 4 (adjustable* from 0 to 15) |      |
| Maximum Ambient Temperature (°C) | 40                                |      |
| Sound Level (dB(A))              | Standard                          | < 66 |
|                                  | Hush Mode*                        | < 62 |

### Greenhouse and Energy Minimum Standards (GEMS)

|                           |                      |  |
|---------------------------|----------------------|--|
| Star Rating               | 7                    |  |
| Product Temperature Class | M1 (-1 to 5°C)       |  |
| Total Energy Consumption  | 1.57 kWh/24 h        |  |
| Annual Running Costs      | \$172 (@ \$0.30/kWh) |  |

### Electrical

|                  |                                                   |  |
|------------------|---------------------------------------------------|--|
| Supply           | 220 to 240 volts a.c., 50 Hz, single phase supply |  |
| Cord             | 1.9 power cord with 3-pin, 10 amp plug            |  |
| Current draw (A) | 2.6                                               |  |

### Refrigeration

|                       |                                         |    |         |
|-----------------------|-----------------------------------------|----|---------|
| Controller            | SCS Connect (SKOPE-connect™ compatible) |    |         |
| System Type           | Removable cartridge                     |    |         |
| Cartridge Weight (kg) | 24                                      |    |         |
| Refrigerant/Charge    | R290/81 g                               |    |         |
| Nominal Capacity (W)  | 650                                     |    |         |
| Heat Rejection (W)    | Average                                 | 65 | Peak 85 |
| Defrost Type          | Automatic, off-cycle                    |    |         |
| Drainage              | No plumbing required                    |    |         |



CL.2.SSW  
on the SKOPE website