

The SKOPE logo is displayed in white, bold, uppercase letters on a red rectangular background.

TMF1500N-Ice 3 Glass Door Upright Display or Storage Freezer

Model ID: TMF1500N-Ice

Heavy duty three glass door ice storage freezer with a higher weight load shelf, powered by ActiveCore technology offering new levels of quiet efficiency. Also features a digital inverter compressor for precise temperature control, active condensation control, and ActiveCore's trademark premium look and build quality.



5 Year Warranty Protection



GEMS Compliant



SKOPE-connect™



Natural Refrigerant



FEATURES & BENEFITS

- Optimised for ice: heavy duty steel shelf and temperature settings
- 25% more efficient than VFX series
- Heavy duty ActiveCore reliability and temperature consistency
- Eco-friendly R290 natural refrigerant technology
- SKOPE-connect app control and convenience – including “hush mode” for quiet running
- Self-closing triple-glazed, lockable door using argon-filled safety glass
- “Frameless” glass door design provides maximum product visibility
- GEMS compliant

SPECIFICATIONS

- Dimensions: 1705 W x 745 D x 2210 H (mm)
- Doors: 3
- Door Type: Glass
- Shelves: 1 (per door)
- Material: Powder coated galvanised steel
- Gross Volume (Litres): 1396
- Total Floor Area (m²): 1.27
- Weight (kg): TBC
- Refrigeration Unit: Self-Contained
- Temperature Range: -9°C to -12°C (adjustable with SKOPE-connect -26°C to -12°C)
- Max Ambient Temperature: 40°C
- Refrigerant: R290 / 107g (natural refrigerant)
- GEMS Class: 3L1
- GEMS Energy Consumption (kWh/24h): 31.12
- GEMS Annual Running Costs: \$3,433 (@ \$0.30/kWh)
- kW: 2.76
- Current Draw (Amps): 11.5
- Electrical Safety Climate Class: 5
- Noise Measurement (dB): ≤ 68dB(A)
- Interior Lighting: 3 × 20 W, 1400 mm LED strip side light
- Sign Lighting: n.a.
- Controller: SCS Connect (SKOPE-connect compatible)
- Connectivity: Bluetooth® wireless technology
- Refrigeration System: Top mounted, integral, removable ActiveCore freezer cartridge
- Power Cord: 2.3 m power cord with 3-pin, 15 amp plug
- Power Supply: 220-240 volts a.c., 50 Hz, single phase supply

OPTIONS